

Uniclass L621 / CI/SfB /

# / Yq2 / April 2014 TECHNICAL INFORMATION POSTCRETE

# Ready-to-use Product Data Sheet

A ready-to-use blend of selected sand, cement and additives formulated for fixing wooden, concrete and metal posts.

# USES

To fix all types of wood, metal and concrete posts.

# DESCRIPTION

POSTCRETE is ready to use. No mixing is required.


## PACKAGING

POSTCRETE is packed in weatherproof plastic packaging.

#### **STORAGE**

POSTCRETE is a cement-based material and should be handled and stored with care. This product may be stored, unopened in either indoor or outdoor conditions. Information on the maximum storage period can be found on the bag.













#### SITEWORK

For best results follow these instructions:

- 1. Dig hole to correct depth and width relevant to post size (see table on reverse).
- 2. Fill hole with water to a third of the depth.
- 3. Pour in POSTCRETE evenly around post until no standing water is visible (powder completely covers water surface). Sprinkle water on top of powder.
- 4. Position and level post as required. Setting will take place in 5 to 10 minutes.
- 5. When set, cover top of hole with soil or grass.

Do not mix POSTCRETE with water by hand or machine. Please consult the table on the reverse for guidance on the quantity of POSTCRETE to use.



#### CLEANING

All equipment should be cleaned with water. Do not flush down drains.

## AVAILABILITY

POSTCRETE is available throughout Great Britain at Tarmac Cement stockists. POSTCRETE is supplied in 20 kg plastic bags.

# **CONDITIONS OF USE**

- POSTCRETE may be used for the purposes of fixing domestic posts.
- POSTCRETE may be used for fixing decking posts, rotary washing lines and small/medium sized gateposts (less than 1.0m width gate).
- POSTCRETE may not be used for general concreting, screeds, mortar, grout or render.
- If a specified compressive strength is required, POSTCRETE should not be used.
- Normal site practice to the relevant British and European Standards should always apply. Tarmac Cement cannot be held responsible where workmanship has not been carried out in accordance with good practice.
- Manual handling should comply with *The Manual Handling Operations Regulations 1992.*

## **TECHNICAL SUPPORT**

Further information and advice on this product and the full range of Tarmac Cement products can be obtained through the contacts listed below.

## **HEALTH AND SAFETY**

Contact between cement powder and body fluids (eg, sweat and eye fluids) may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheets.

Post size	Hole size (width x depth)	Number of bags required
Round 5cm (2")	15cm (6") x 30cm (12")	1/ <sub>3</sub> bag
	15cm (6") x 45cm (18")	$^{1}/_{2}$ bag
	15cm (6") x 60cm (24")	<sup>3</sup> / <sub>4</sub> bag
	20cm (8") x 30cm (12")	$^{2}/_{_{3}}$ bag
	20cm (8") x 45cm (18")	1 bag
	20cm (8") x 60cm (24")	$1^{1}/_{2}$ bags
	15cm (6") x 45cm (18")	1/3 bag
Square 7.5cm (3")	15cm (6") x 60cm (24")	1/2 bag
	15cm (6") x 75cm (30")	$^{3}/_{4}$ bag
	20cm (8") x 45cm (18")	<sup>3</sup> / <sub>4</sub> bag
	20cm (8") x 60cm (24")	1 bag
	20cm (8") x 75cm (30")	$1^{1}/_{3}$ bags
	25cm (10") x 45cm (18")	$1^{1}/_{2}$ bags
	25cm (10") x 60cm (24")	2 bags
	25cm (10") x 75cm (30")	21/2 bags
	30cm (12") x 45cm (18")	21/ <sub>4</sub> bags
	30cm (12") x 60cm (24")	3 bags
	30cm (12") x 75cm (30")	3³/ <sub>4</sub> bags
Square 10cm (33/4")	15cm (6") x 45cm (18")	$^{1/4}$ bag
	15cm (6") x 60cm (24")	1/ <sub>3</sub> bag
	15cm (6") x 75cm (30")	1/2 bag
	20cm (8") x 45cm (18")	$^{2}/_{_{3}}$ bag
	20cm (8") x 60cm (24")	<sup>3</sup> / <sub>4</sub> bag
	20cm (8") x 75cm (30")	1 bag
	25cm (10") x 45cm (18")	$1^{1}/_{2}$ bags
	25cm (10") x 60cm (24")	$1^{3}/_{4}$ bags
	25cm (10") x 75cm (30")	2 bags
	30cm (12") x 45cm (18")	2 bags
	30cm (12") x 60cm (24")	2³/ <sub>4</sub> bags
	30cm (12") x 75cm (30")	$3^{1}/_{2}$ bags

For futher information

*Technical helpdesk Tel: 0845 812 6232 E-mail info-cement@tarmac.com* 

# Customer services & sales

Tel: 0845 812 6300

E-mail customerservice@tarmac.com

'Tarmac' and the 'circle logo' are registered trademarks. ©2016 Tarmac Trading Limited.

The information in this data sheet is accurate at the time of printing, but Tarmac reserves the right to amend details as part of its product development programme. The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.